

IN THE CLAIMS:

The following is a complete listing of claims in this application.

1. (currently amended) A compound sound generator for an information equipment comprising:

a case of the equipment, the case having an inner surface;

a frame set in the case;

a speaker and receiver provided in the frame, the speaker having a first diaphragm and the receiver having a second diaphragm;

a first protector and a second protector, each having sound discharge holes, secured to the frame for protecting the first diaphragm and the second diaphragm, respectively;

a first back chamber behind the first diaphragm of the speaker and a second back chamber behind the second diaphragm of the receiver; and

first and second annular spacers provided between the inner surface of the case and the outer surfaces of the first protector and second protector, respectively, so as to surround the sound discharge holes of the protectors;

openings provided in the frame to communicate the first and second back chambers with the inside space of the case so as to discharge sounds generated in the first and second back chambers;

a baffle formed on a part of provided between the inner surface of the case and an outer surface of the frame for dividing the case so as to separate the first and second back chambers from each other so as to prevent airflow from one of the back chambers from flowing into the other back chamber.

2. (currently amended) The compound sound generator according to claim 1 wherein one of the first and second back

~~chambers of the speaker and the receiver is opened to the outside of the case, the other chamber is opened to the inside of the case the baffle is formed as a part of the frame.~~

3. (currently amended) The compound sound generator according to claim 2 1 wherein the first back chamber of the speaker is opened to the outside of the case.

4. (currently amended) The compound sound generator according to claim 3 1 wherein the second back chamber of the receiver is opened to the outside of the case at a same surface as a surface where a sound discharge opening of the speaker is formed.

5. (currently amended) The compound sound generator according to claim 3 wherein the ~~first~~ second back chamber of the receiver is opened to the outside of the case at a surface different from a surface where a sound discharge opening of the speaker is formed.